

PointGuard Communication Module

- NEMA 4X enclosure type, more reliable
- Plug & play, easy to use
- Supports 3G / 4G communication



PointGuard Communication Module

PG CommMod		Units
Connection interface	USB	
Installation type	Plug-and-play	
Display	LED indicators	
Dimensions (W / H / D)	2.05 × 4.41 × 1.30 / 52 × 112 × 33	in / mm
Weight	0.2 / 90	lbs / g
Enclosure type	IP66	
Power consumption (typical)	< 4	W
Supported standards	4G : LTE-FDD (B2 / B4 / B5 / B12 / B13 / B14 / B66 / B71) 3G : WCDMA (B2 / B4 / B5)	
Storage temperature range	-40 ~ 158 / -40 ~ 70	°F / °C
Operating temperature range	-22 ~ 140 / -30 ~ 60	°F / °C
Relative humidity range	0% ~ 95%	
Max. operating altitude	13123 / 4000	ft / m
Controller compatibility	PointGuard Energy Controller series	

Disclaimer: The information on this file is provided on an "as is" basis. To the fullest extent permitted by law, PointGuard Energy Inc. excludes all representations and warranties relating to this file and its contents or which is or may be provided by any affiliates or any other third party, including in relation to any inaccuracies or omissions in this file.